

**FLAT WEBBING AND POLYESTER ROUNDSLING WORKING LOAD CHART**

**FEATURES**

- All slings are made from 100% Polyester.
- WLL is clearly marked on each sling.
- Colour coding on each sling for added safety.
- Protective sleeves are recommended for lifting sharp and rough objects.

**FLAT SLINGS**

Manufactured to A.S.1353 Parts 1 & 2, Safety Factor 8:1

**ROUND SLINGS**

Manufactured to A.S. 4497.1, Safety Factor 7:1



M = 1.0



M = 0.8



M = 2.0



M = 1.9



M = 1.7



M = 1.4



M = 1.0



M = 1.7



M = 1.4

COLOUR	VERTICAL	CHOKE	BASKET	30°	60°	90°	120°	60°	60° CHOKE
CODE	WLL kg	WLL kg	WLL kg	WLL kg	WLL kg	WLL kg	WLL kg	WLL kg	WLL kg
VIOLET	1000	800	2000	1900	1700	1400	1000	1700	1400
GREEN	2000	1600	4000	3800	3400	2800	2000	3400	2800
YELLOW	3000	2400	6000	5700	5100	4200	3000	5100	4200
GREY	4000	3200	8000	7600	6800	5600	4000	6800	5600
RED	5000	4000	10000	9500	8500	7000	5000	8500	7000
BROWN	6000	4800	12000	11400	10200	8400	6000	10200	8400
BLUE	8000	6400	16000	15200	13600	11200	8000	13600	11072
ORANGE	10000	8000	20000	19000	17000	14000	10000	17000	14000
ORANGE	12000	9600	24000	22800	20400	16800	12000	20400	16800
ORANGE	15000	12000	30000	29500	25500	21000	15000	25500	21000
ORANGE	20000	16000	40000	38000	34000	28000	20000	34000	28000
ORANGE	30000	24000	60000	57000	51000	52000	30000	51000	52000
ORANGE	50000	40000	100000	95000	85000	70000	50000	85000	70000

Note ~ The maximum WLL is determined by the sling angle.

**INSPECTION REGISTRIES**

- All flat and round slings should be visually inspected at 3-monthly intervals as per Australian Standards.



**YUPPIE STRAPS**



Black attachment strap complete with 'D' rings each end, rated at 250kg WLL, various colours and lengths can be made to order.

