

# Single and 3 Phase Pacific Electric Winches

Capacities: 200kg to 5000kg

Precision engineered, ruggedly constructed and available in a range of single and three phase models suitable for many hoisting and pulling operations.

### FEATURES

- High performance with low maintenance and adjustment free brakes.
- Brakes designed for both static and dynamic loading automatically apply in the event of power loss.
- Compact load sharing design of the heat treated planetary gear ensures quiet operation and long life.
- Low voltage (24v) push button control supplied as standard on three phase models.

COMPLIES WITH AS1418.2

Model Code	Capacity kg	Speed m/min	Motor kW	Voltage x phase	Wire rope ømm x m	Weight kg
CP - 200	200	10 - 15	0.6	240 x 1	6 x 30	32
CP - 250	250	10 - 15	0.75	240 x 1	6 x 30	34
CP - 300	300	10 - 15	1.15	240 x 1	6 x 30	37
CWG - 10077	300	12 - 17	1.5	240 x 1	7 x 40	44
CWG - 30075	300	10 - 15	0.75	415 x 3	6 x 30	34
CWG - 10151	400	12 - 18	1.5	250 x 1	9 x 60	120
CWG - 30151	500	12 - 18	1.5	415 x 3	9 x 60	120
CWG - 30265	650	12 - 18	2.2	415 x 3	9 x 60	160
CWG - 30375	900	13 - 20.6	4	415 x 3	10 x 60	220
CWG - 30565	1100	14 - 25	5.5	415 x 3	12 x 100	290
CWG - 30750	2200	7 - 12	5.5	415 x 3	16 x 100	450
CWG - 31500	3500	6.3 - 8	5.5	415 x 3	18 x 120	860
CWG - 34000	5000	8 - 11.2	11	415 x 3	22.4 x 150	1500



CP 200 - 300kg

Model Code	A mm	B mm	C mm	D mm	E mm	F mm
CP - 200	4 x ø10.5	142	142	548	210	241
CP - 250	4 x ø10.5	142	142	548	210	241
CP - 300	4 x ø10.5	142	142	548	210	241
CWG - 10077	4 x ø13.5	197	156	630	240	300
CWG - 30075	4 x ø10.5	142	142	548	210	241
CWG - 10151	4 x ø16	400	325	922	367	425
CWG - 30151	4 x ø16	400	325	922	367	425
CWG - 30265	4 x ø16	400	325	940	367	425
CWG - 30375	4 x ø19	500	370	1009	400	445
CWG - 30565	4 x ø19	620	495	1120	470	520
CWG - 30750	4 x ø22	600	499	1246	565	658
CWG - 31500	8 x ø30	847	680	1439	740	860
CWG - 34000	8 x ø32	920	680	1860	740	905



CWG 300 - 650kg

